



## C Series

# IB9369 (2.8 mm)

2MP Outdoor Bullet Network Camera



## Technical Specifications

System Information	
CPU	Multimedia SoC (System-on-Chip)
Flash	256MB
RAM	256MB
Camera Specifications	
Image Sensor	1/3.1" Progressive CMOS
Max. Resolution	1920x1080 (2MP)
Lens Type	Fixed-focal
Focal Length	f=2.8mm
Aperture	F2.0
Iris Type	Fixed iris
Field of View	f=2.8mm 118° (Horizontal) 65° (Vertical) 140° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Enhanced
Day/Night	Yes
Removable IR-cut filter	Yes
Illuminators	Built-in IR illuminators, effective up to 30 meters with Smart IR, IR LED*1
Minimum Illumination	0.08 lux @ F2.0 (Color) <0.005 lux @ F2.0 (B/W) 0 lux with IR illumination on
Tilt Range	90°

Rotation Range	180°
Pan/Tilt/Zoom Functionalities	ePTZ: 18x digital zoom (4x on IE plug-in, 4.5x built-in)
Storage	Seamless Recording to MicroSD/SDHC/SDXC card slot (128GB capacity supported) and recording to network-attached storage (NAS)

Video	
Compression	H.265, H.264, MJPEG
Maximum Frame Rate	30 fps @ 1920x1080
Maximum Streams	2 video streams (Up to 7 configurable profiles)
S/N Ratio	59 dB
Dynamic Range	WDR Support
Video Streaming	Adjustable resolution, quality and constant bit rate control, Smart Stream III
	General settings video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings
	Illuminators illuminators, anti-overexposure
	Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR
	Exposure BLC, HLC, exposure control (exposure level, exposure time, gain control), AE speed adjustment, WDR
	Privacy mask Scheduled profile settings Pixel calculator
Image Settings	

Network	
Users	Live viewing for up to 10 clients
Security	Access list, digest authentication, HTTPS, IEEE 802.1x, password protection, signed firmware, user access log, user account management
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2, UDP, UPnP
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T supported, specification available at <a href="http://www.onvif.org">www.onvif.org</a>

AI Analytics	
Vision Object Analytics	Path Extraction
Application	Five-window video motion detection, people detection, vehicle detection, time filter

Solution Integration	
Video Motion Detection	Motion Detection (Five-window video motion detection)

Alarm and Event	
Event Trigger	Camera tampering detection, Manual trigger, Motion detection, Periodical trigger, Recording notification, SD card life expectancy, System boot

Event Action	Event notification via email, HTTP, FTP, SFTP, NAS server, SD card, push notification File upload via email, HTTP, FTP, SFTP, NAS server, SD card
--------------	--

General	
Connectors	RJ-45 cable connector for 10/100Mbps Network/PoE connection
LED Indicator	System power and status indicator
Power Input	IEEE 802.3af Class 0 PoE, DC 12V (Simultaneous Power Redundancy Supported)
Power Consumption	PoE: Max. 6W/4W (IR on/off) DC 12V: Max. 5.1W/3.4W (IR on/off)
Dimensions	ø 91.1 x 181.5 mm
Weight	671g
Certifications	EMC CE (EN55032 Class A,EN55035), FCC (FCC Part 15 Subpart B Class A), ICES-003 issue 7, RCM (AS/NZS CISPR 32 Class A), VCCI (VCCI-CISPR 32 Class A) Safety UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 62471, IEC/EN 60950-22) IA BIS (IS 13252): BSMI Environment IK10 (IEC 62262), IP66 (IEC 60529)
Operating Temperature	Starting Temperature: -30°C ~ 50°C (-22°F ~ 122°F) Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F) (IR off) -30°C ~ 50°C (-22°F ~ 122°F) (IR on)
Humidity	95% RH (non-condensing)

System Requirements	
Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above Internet Explorer 10/11
Other Players	VLC: 1.1.11 or above

Included Accessories	
Packing Contents	Quick installation guide, alignment sticker, screw pack, cable gland

